

10-03-00

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Attorney Docket No.: 1441-6

CERTIFICATE OF MAILING OR TRANSMISSION

"Express Mail" mailing label number: EK111030037US

Date of Deposit: October 2, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" under 37 CFR, Section 1.10 on the date indicated above and is addressed to Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231 by

  
Signature

BOX PATENT APPLICATION  
ASSISTANT COMMISSIONER FOR PATENTS  
WASHINGTON, DC 20231

Sir:

Enclosed for filing is the patent application of:

Inventors: Paul A. Bolme and Mark W. Bolme

Title: NATURAL LANGUAGE MESSAGES FROM A KEYSTROKE OUTPUT  
WEDGE

Including:

- ☒ 1. A specification including claims consisting of 22 pages.
- ☒ 2. Drawings consisting of 3 sheets.
- ☒ 3. Declaration and Power of Attorney.

Additionally:

- ☐ 4. An assignment of the invention to \_\_\_\_\_ is attached.
- ☒ 5. Applicants have small entity status.
- ☒ 6. A filing date in accordance with 37 CFR 1.10 is requested (Express mail certificate is part of this transmittal letter).

X 7. COMPUTATION OF FEE

Claims	Number Filed	Number Extra		Basic Fee \$710/\$355
Total	70 - 20=	50	x\$18/\$9=	\$450.00
Indep.	5 - 3=	2	x\$80/\$40=	\$80.00
Multi Dep.	xxx	xxx	x\$260/\$130=	
TOTAL Filing Fee:				<u>\$885.00</u>

Assignment Recording Fee (\$40.00): \$ .00

- X 8. Check No. 15926 for \$885.00 for filing fee is enclosed.  
\_\_\_ 9. Check No. \_\_\_ for \$.00 for assignment fee is enclosed.  
\_\_\_ 10. No fee is enclosed at this time.  
X 11. Charge any additional fees to Deposit Account No. 07-1897.  
X 12. A copy of this letter is enclosed.  
X 13. A postcard is enclosed as acknowledgment of receipt of this application.

Respectfully submitted,

GRAYBEAL JACKSON HALEY LLP

*CB Villani*

Christopher B. Villani  
Registration No. 38,355  
155-108th Avenue N.E., Suite. 350  
Bellevue, WA 98004-5901  
(425) 455-5575

## NATURAL LANGUAGE MESSAGES FROM A KEYSTROKE OUTPUT WEDGE

### TECHNICAL FIELD

5           The invention relates generally to a computer system with a software wedge for data entry of bar code symbols into a computer software application designed for keyboard input, and more particularly to a method and computer system that provides natural language messages from a software wedge to a bar code scanner user.

10

### BACKGROUND

Bar code scanners are used extensively in commercial applications such as scanning grocery items at a supermarket, or tracking parts in a warehouse environment. The scanners are typically a stationary unit, like the type at a supermarket checkout counter, a scanner tethered to a computer by a cable, or a handheld unit that a user can walk around with and scan items where they are stored (on a warehouse shelf for instance). The data from the scanned bar code is usually transmitted by wired or wireless mediums to an application program running on a local computer.

20           Many scanning systems, which include a scanner, a computer and software running on the computer for receiving the scanned information, provide the user some form of audible or visual feedback. Depending on the sophistication of the scanning system, the messages conveyed by such feedback range from a simple

confirmation that a particular scan was error free to messages providing a user with detailed system status messages and prompts for scanning activity by the user.

Many business operations, such as shipping and receiving operations for example, demand an efficient and accurate method of capturing data relating to those operations. Instead of supplying the required data by entering keystrokes, which is a slow method and susceptible to human error, a bar code scanner is often used to scan a label containing the required information in an encoded format.

However, many computer software applications for such operations are designed to accept only keyboard input. To enable entry of bar code data into data fields for such a keyboard-based application program, a device called a "wedge" is used.

Typically the wedge is a hardware device incorporating bar code scanning equipment, and placed between the keyboard and the keyboard input port on a terminal or computer. The function of the wedge is to translate or convert the bar code data into keystroke data, because that is what is expected by standard keyboard-based applications. In other words, the hardware wedge emulates keystrokes.

Some fully-integrated scanning systems, which include expensive custom, non-standard software applications, are designed to receive scanner input without using a hardware wedge. Such systems typically provide users with more extensive feedback than merely indicating that a scan was successful or the scanner is ready for a new scan like some traditional hardware wedges. These systems traditionally have displays for presenting a user with prompts and other kinds of feedback.

However, such systems will not work with standard keyboard-based applications, which require a wedge, and hardware wedges themselves do not have the capability to generate sophisticated messages to the user because the keyboard ports that

hardware wedges connect to are uni-directional. In other words, a traditional hardware wedge passes data in only one direction; from the port or scanner to the keystroke input buffer. Therefore, hardware wedges are not able to interact with a keyboard-based application to transmit messages to the user. Also, the form of message conveyed to a user from a hardware wedge is typically limited to a simple pattern of tones and/or flashing lights.

Accordingly, there is a need for a keystroke output wedge that can perform the keystroke emulation function of a standard hardware wedge, but can also provide the user a wide variety of sophisticated natural language messages without having to create custom software or modify a standard keyboard-based software application that is designed to receive keystroke data inputs.

## SUMMARY

The present invention is a keystroke output wedge (also referred to hereinafter as a "wedge"), implemented in software or firmware, that provides natural-language messages to a user. The wedge provides the data conversion function of a typical hardware wedge, namely, the translation of bar code input data into keystroke output data for use in a typical keyboard-based application program. But, it can also provide sophisticated natural language feedback to the user in audible or visual form. For example, the keyboard output wedge may return the confirmation message "VALID SCAN, SCAN PART NUMBER NEXT" when the user scans a particular bar code.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an schematic depiction of an embodiment of the present invention including a computer, a scanner and peripheral devices.

FIG. 2 is a depiction of the transaction definition window used to define  
5 various data field parameters and natural language messages.

FIG. 3 depicts a definition window for wedge options used to define natural language message file locations.

## DETAILED DESCRIPTION

### 10 Overview:

The present invention is a keystroke output wedge (also referred to hereinafter for brevity as a "wedge"), implemented in software or firmware, that provides natural-language messages to a user. The wedge provides the data translation function of a typical hardware wedge, namely, the translation of bar code  
15 input data into keystroke output data for use in a typical keyboard-based application program. But, it can also provide sophisticated natural language feedback to the user in audible or visual form. For example, the wedge may return an audible or visible confirmation message "VALID SCAN, SCAN PART NUMBER NEXT" when the user scans a particular bar code.

20 The invention allows a user to work with a scanner to provide multiple kinds of input (e.g., numbers, letters, or different formats of numbers or letters) to a keyboard-based application program without constantly referring to information on a computer display for guidance or prompting. For example, the user can work with a remote wireless scanner while wearing wireless headphones to receive natural language

messages sent by the wedge. Or, the user can view a text message on a display incorporated into the scanner he or she is using.

The wedge can determine a variety of states of the keyboard-based application program or computer operating system (O.S.) and convey a message in natural language to a user as a function of the state of the application or the O.S. An example is the case of a product shipping application. Such an application may require the entry of several data fields to complete the shipping transaction. The fields may be "PURCHASE ORDER NUMBER," "PART NUMBER," and "QUANTITY." The wedge program monitors the readiness of the application for a particular data type through operating system queries. At the appropriate time, the wedge will convey a prompt message, which solicits an action from the user, such as "SCAN PART NUMBER." This may be followed by a combined feedback and prompt message such as, "VALID SCAN, SCAN QUANTITY."

Alternatively, the user may desire to switch applications. This could be done manually (by selecting a new window to come to the front of a display screen) or by scanning a command code to bring a new window to front, thereby activating a new transaction, whereupon the wedge might return, "INVENTORY TRANSACTION READY, SCAN PARTS BIN NUMBER," to confirm to the user that the desired application is running and to prompt for, or solicit, entry of a specific type of information. Yet another example is the case where the scan is valid but the host application is not responding. The message might contain confirmation and status messages such as: "VALID SCAN, APPLICATION NOT RESPONDING, CHECK HOST COMPUTER."

Referring now to FIG. 1, the schematic diagram depicts a computer 110 and a bar code input device 112, (scanner) configured to implement the method of the

present invention. The computer 110 includes an operating system (OS) 114, a  
keystroke output wedge software program 116, a keyboard-based application  
program 118, a keyboard 120, a communications port 122, a memory 124 and a  
monitor or display 126 and, in some embodiments, a remote audio output 127  
5 (speakers) and a remote display 128, such as an LED panel on a scanner.

The computer 110 may be of a typical desktop PC type, a laptop or a special  
purpose computer designed more specifically for portable data collection  
applications. The bar code input device may alternatively be any data input device  
that provides a data stream to the computer that is readily convertible to keystroke  
10 data, such as a scale or bar code scanner. For the purposes of this description the  
word "scanner" is intended to mean a device for scanning bar codes, or any other  
data input device. An example of a suitable scanner to use in the present invention  
is the Intermec 1551 laser scanner. The communications port may be an RS-232  
serial port, a USB port, an infrared port, or other portal for communicating with the  
15 computer. The principle criterion is that the scanner 112 be capable of transmitting  
data to the communications port 122.

The present invention will be described in the context of the Microsoft  
Windows NT 4.0 operating system, but it is understood that other operating systems,  
such as LINUX and Apple's System 8.0 for example, are suitable for practicing the  
20 invention. Contained in the Windows OS 114 is a complete API 123 (Application  
Program Interface) allowing application programs to obtain and exchange  
information concerning the operating state of the computer. (For more information  
on this API, refer to Microsoft's Win32 Programmer's Reference, Volumes 1 through  
5.) The memory 124 may be a typical hard drive, a floppy disk, a CD or DVD, or



other computer readable media for storing applications programs, the O.S. or other computer program code.

#### Configuration Manager:

5           Before the process of scanning begins, the user must define how he will use the scanner to complete a data collection process or "transaction." This is done using the Configuration Manager module 130 which is part of the wedge 116 indicated in FIG. 1.

10           A particular set of data is required to complete a transaction in the application program 118. For instance, to complete a Purchase Order fulfillment transaction, a Purchase Order number may need to be entered in a field in the application program 118 along with other information such as Part Numbers and Quantities. FIG. 2 illustrates a Transaction Definition window 200, presented by the Configuration Manager module 130. The Transaction Definition window is used to setup the  
15           various parameters relating to different data fields to be collected by the user and the types of messages that may be transmitted to the user depending on variables such as the state of the application program or the quality of the scan.

          The Transaction Definition includes the following fields and controls. A descriptive Transaction Name field 202, in this case "PURCHASE ORDER  
20           FULFILLMENT. The next field is the Window Title field 204, which identifies the name of the window in the keyboard-based application program into which the transaction information is entered. This is followed an Initial Keystrokes field 206, which defines the initial keystrokes to be entered before the first data field is filled in, such as a leading {SPACE BAR} entry. Next is a Transaction Prompt field 208,  
25           which defines the message to be conveyed to the user. In this case, a computer

audio WAV file called "POfill.wav" is transmitted to the remote audio output 127 (speakers) indicating that the transaction is active. Alternatively, a text file could be transmitted to remote display 128 which may be a LCD screen for example a handheld wireless scanner.

5           The next section of the Transaction Definition window 200 is used to define the various data items or fields in the application program that are required to complete the transaction, their associated messages and other parameters. A Field Name field 210 identifies the name of the field in the application program, (e.g., "PURCHASE ORDER NUMBER." A Field Mask field 212 is next. The field mask  
10   value in the Field Mask field 212 is used to error-check the data supplied for that field identified in the Field Name field 210. Next is the Exit Keystrokes field 214. The field defines the keystrokes to be entered after the data field is filled in. For example, once the "PURCHASE ORDER NUMBER" field is filled in, a "{TAB}" keystroke will be transmitted to the application program that will cause the next field in the  
15   application program to be set to receive data, for instance, a "PART NUMBER" field. The Audio Prompt field 216 contains the identifies the WAV file to be run when the application program is ready to gather that data for that field defined in Field Name 210. This is followed by an Error Message field 218 which defines the WAV file to be run if the input data does not pass the error checking (i.e., does not fit the field mask  
20   value).

Next are the Character Stripping Controls 220 which establish the number of characters that need to be stripped from the front or back of the bar code data before the data is entered into the application. As an example, a company may have part number bar codes on all inventory that consists of the letters "PN" followed by the  
25   part number. These two letters allow the bar code to be error checked to make sure

it starts with "PN," but the letters "PN" must be stripped off before the part number is sent as keystrokes to the PC application. Depicted, but not described, are additional controls for setting up additional fields, etc. Now referring to FIG. 1, the Configuration Manager 130 writes all the information out to a Configuration File 132.

- 5 The Configuration File 132 is loaded into the Configuration Manager 130 whenever the wedge program 116 is run.

#### Bar Code Input Device

- 10 When a bar code is scanned, the bar code is decoded by the scanner and a carriage return (ASCII value 13) is appended. The result is passed as ASCII data to the communications port 122 where it is received and stored by Windows. Windows makes this data available to the wedge program 116 through a Windows Communications API 117.

- 15 Data Translation and Buffering:

- 20 Certain bytes of data that are received in the serial port may not correspond to keystrokes. For instance, the scanner is configured to append special characters, such as a carriage return, to the end of each scan. This is to be used to indicate that a scan is complete, and any further data will be coming from the next scan. The receiving application may be programmed to receive an "ENTER" keystroke following the input of data, or a "TAB" keystroke, or no keystroke at all. In addition, the wedge might be required to drop certain characters, pass multiple keystrokes to the application, or execute a command when a single character is received. The purpose of the Data Translation module 134 is to translate the serial input into the  
25 desired application program input and also sort out the commands and pass them to

the Command Execution module 136. At approximately the same time, the remaining data is passed to the Data Buffering module 138 for storage until the Data Checking module 140 is ready for the data. The Data Translation module 134 uses an MS COM object to interface with the Windows Communications API 117. The

5 Data Translation module 134 is informed by an O.S. event that data is available. The data is retrieved using the input "method" (in this context "method" is a programming term associated with MS COM,) of the MS COM object. (For general reference regarding MS COM, see Microsoft Visual Basic 6.0 Controls Reference.)

#### 10 Command Execution:

When the Command Execution module 136 is informed by the Data Translation module 134 that a carriage return character (ASCII value 13) has been received, the Command Execution module 136 knows that a scan has ended and informs the Data Checking module 140 that the Data Checking module 140 needs to

15 perform error checking on the data being stored in the Data Buffering module 138. Other commands can be executed by setting the Data Translation module to look for specified command characters in the input data stream and passing these commands to the Command Execution module. Other commands can be defined, such as one that brings a new window to the front, requests a repeat of a previous

20 prompt, or runs an application.

#### Data Checking

The Data Checking module 140 keeps track of which transaction (e.g., PURCHASE ORDER FULFILLMENT) is being worked on, and for which data field

25 (e.g., PURCHASE ORDER NUMBER) data is being gathered. If the currently active

window on the host computer 110 (see Window Monitor, below) is not a window intended to collect transaction data, an audible natural language message is played informing the user (e.g., "INVALID WINDOW"). As shown in FIG. 3, a wedge options window 300 provides a means for defining the WAV files to be played in the

5 instances of an invalid window 302 or a completed transaction 304.

Once the currently active window is the correct window for the current transaction data collection activity, the Data Checking module 140 uses the field mask value (see Field Mask 212 above) to check the data for accuracy. If the scanned data does not fit the field mask value, the Data Checking module 140

10 causes an audible natural language message to be transmitted to the user (e.g., "INVALID PURCHASE ORDER NUMBER"). This message informs the user that the scan was not acceptable, and gives positive feedback to the user regarding what would be acceptable. The audible natural language message is communicated to the user by calling the Windows Sound API 147 with the "sndPlaySound" function

15 (ref. Microsoft Win32 Programmer's Reference). The message is identified in the Error Message field 218 discussed above in Configuration Manager section.

#### Field Mask:

The field mask value of the Field Mask 212 is used to check the incoming

20 data to ensure that the proper bar codes are being scanned. The field mask may include characters with special meanings. Examples of special characters that may be used in the field mask and their meanings are shown in Table 1.

Table 1.

@	This character matches upper- and lower-case a-z only.
#	This character equals the numeric digits from 0-9.
?	This character will accept any printable character.
~	This is a prefix that indicates that any number of the following characters are acceptable (even zero).

All other characters in the mask are treated literally. For example, assume the user wants to scan a part number for a given field and all the part numbers begin with the letters "PN," which is followed by one or more digits (e.g. "PN1234"). If the field mask value is set to "PN", only scans that are exactly "PN" will be accepted hence, "PN1234" wont be accepted because it contains additional characters, namely, "1234." But, if the field mask value is set to "PN~?", then, per the rules established in Table 1, the scan will be accepted as valid because it starts with "PN" and the following string of characters "1234" are printable.

#### Keystroke Manager:

The Keystroke Manager module 142 is responsible for transmitting the keystroke data to the windows application. The data is transmitted by repeatedly calling the Windows Keyboard API 144 using the "keybd\_event" function.

#### Window Monitor:

The purpose of the Window Monitor module 146 is to detect which transaction is represented by the foremost window. (In a keyboard environment, the foremost window, alternatively the currently active window, is the one to which keystrokes will

be sent. In most computer systems, the currently active window can be viewed on the monitor. If there are multiple open windows, the currently active window can usually be viewed as the topmost or foremost window, or it may be differentiated by a color scheme that contrasts with other open, but not active, windows.) The

- 5 Window Monitor module 146 performs its function by monitoring the title of the foremost window and comparing the title to the values entered in the Window Title field 204 of the Transaction Definition 200. The Window Monitor module 146 repeatedly queries (e.g., 20 times per second) the Windows API 148 using the functions "GetForegroundWindow" and "GetWindowText" (ref. Microsoft Win32
- 10 Programmer's Reference) to determine which window is foremost and the title of that window. If a new window is brought to the forefront, the Window Monitor module 146 consults the transaction definitions in the Configuration Manager 130 to find a transaction with the same title as new foremost window. If no transaction exists for the new window, the Data Checking module 140 is informed. If any scan is received
- 15 at that time, the Invalid Window WAV file 302 is played. If a transaction definition exists that matches the window title, values are set that inform the Data Checking module 140 which transaction the application program is ready to process. A natural language message is then transmitted to the user (e.g., "PURCHASE ORDER FULLFILLMENT TRANSACTION READY, SCAN PURCHASE ORDER NUMBER")
- 20 informing the user of the status of or feedback regarding the application program and prompting the user to provide data.

As indicated by the foregoing description, many alternative configurations of software are possible to create embodiments of the invention. Consequently, the invention should not be limited by the foregoing description and should be viewed as

25 broadly as the following claims.

We claim:

1. A method for presenting a natural language message to a user from a keystroke output wedge, the method comprising:

5 a) receiving input data in a keystroke output wedge;  
b) processing the input data;  
c) correlating the processed data with a natural language message stored in a memory;

10 c) providing from the keystroke output wedge to a user the natural language message;

d) converting the input data into keystroke data; and  
e) transmitting the keystroke data out of the keystroke output wedge.

15 2. The method of claim 1 wherein the natural language message is provided audibly.

3. The method of claim 1 wherein the natural language message is provided visually.

20 4. The method of claim 1 wherein the natural language message is provided at a pre-selected time.

5. A method for presenting a natural language message to a user from a keystroke output wedge, the method comprising:

25 a) receiving in a keystroke output wedge information from an operating system; and

b) providing a natural language message from the keystroke output wedge to a user as a function of the information received from the operating system.

30 6. The method of claim 5 further comprising the step of querying the operating system for information.



7        The method of claim 6 wherein the information relates to an application  
program designed to receive keystroke input.

5        8.        The method of claim 6 wherein the natural language message is a  
prompt soliciting the user to provide input.

9.        The method of claim 6 wherein the natural language message is  
feedback provided in response to input received from the user.

10        10.        The method of claim 6 wherein the natural language message is a  
status message provided to the user in response to a pre-programmed inquiry from  
the keystroke output wedge to the operating system.

15        11.        The method of claim 5 wherein the natural language message is  
provided audibly.

12.        The method of claim 5 wherein the natural language message is  
provided visually.

20        13.        A method for presenting a natural language message to a user from a  
keystroke output wedge, the method comprising:

25        a)        querying an operating system for information,  
b)        receiving in a keystroke output wedge information from the operating  
system; and  
c)        providing to a user from the keystroke output wedge a natural language  
message, where the natural language message is a function of the information from  
the operating system.

30        14.        The method of claim 13 wherein the information relates to an  
application program designed to receive keystroke input.

15.        The method of claim 14 wherein the natural language message is a  
prompt soliciting the user to provide input.

16. The method of claim 14 wherein the natural language message is feedback provided in response to input received from the user.

17. The method of claim 14 wherein the natural language message is a status message provided to the user in response to a pre-programmed inquiry from the keystroke output wedge to the operating system.

18. The method of claim 13 further comprising the steps of:

- d) converting user input data into keystroke output data; and
- e) transmitting the keystroke output data to an operating system.

19. A method for presenting a natural language message to a user from a keystroke output wedge and converting input data from an input device into keystroke data, the method comprising:

- a) querying an operating system for information,
- b) receiving in a keystroke output wedge information from an operating system;
- c) providing to a user from the keystroke output wedge a natural language message, where the natural language message is a function of the information from the operating system;
- d) converting user input data into keystroke data; and
- e) transmitting the keystroke data to an operating system.

20. The method of claim 19 wherein the information relates to an application program designed to receive keystroke input.

21. The method of claim 20 wherein the natural language message is a prompt soliciting the user to provide input data.

22. The method of claim 20 wherein the natural language message is feedback provided in response to input data received from the user.

23. The method of claim 20 wherein the natural language message is a status message provided to the user in response to a pre-programmed inquiry from the keystroke output wedge to the operating system.

5 24. The method of claim 19 further comprising receiving in a keystroke output wedge input data from a data input device.

25. The method of claim 24 wherein the data input device is a bar code data input device.

10

26. A method for presenting a natural language message to a user from a keystroke output wedge, the method comprising:

- a) querying a Windows-type operating system for information;
- b) transmitting to a Windows API a query for information from a keystroke

15

output wedge;

- c) receiving in the keystroke output wedge information from the Windows-type operating system in response to the query; and

- d) providing to a user from the keystroke output wedge a natural language message, where the natural language message is a function of the information from

20

the operating system.

27 The method of claim 26 wherein the information relates to a Windows-type application program designed to receive keystroke input.

25 28. The method of claim 27 wherein the natural language message is a prompt soliciting the user to provide input data.

29. The method of claim 27 wherein the natural language message is feedback provided in response to input data received from the user.

30

30. The method of claim 27 wherein the natural language message is a status message provided to the user in response to a pre-programmed inquiry from the keystroke output wedge to the operating system.

31. The method of claim 26 further comprising receiving in a keystroke output wedge input data from a data input device.

5           32. The method of claim 26 wherein the data input device is a bar code data input device.

33. The method of claim 26 where the step of transmitting to a Windows API further includes transmitting a GetForegroundWindow function.

10

34. The method of claim 26 where the step of transmitting to a Windows API further includes transmitting a GetWindowText function.

35. The method of claim 26 where the step of providing to a user from the keystroke output wedge a natural language message further includes transmitting to a Windows API a sndPlaySound function.

15

36. A computer program capable of performing the method of claim 1 embodied in a computer readable medium.

20

37. A computer program capable of performing the method of claim 2 embodied in a computer readable medium.

38. A computer program capable of performing the method of claim 3 embodied in a computer readable medium.

25

39. A computer program capable of performing the method of claim 4 embodied in a computer readable medium.

40. A computer program capable of performing the method of claim 5 embodied in a computer readable medium.

30

41. A computer program capable of performing the method of claim 6 embodied in a computer readable medium.

42. A computer program capable of performing the method of claim 7 embodied in a computer readable medium.

43. A computer program capable of performing the method of claim 8 embodied in a computer readable medium.

44. A computer program capable of performing the method of claim 9 embodied in a computer readable medium.

45. A computer program capable of performing the method of claim 10 embodied in a computer readable medium.

46. A computer program capable of performing the method of claim 11 embodied in a computer readable medium.

47. A computer program capable of performing the method of claim 12 embodied in a computer readable medium.

48. A computer program capable of performing the method of claim 13 embodied in a computer readable medium.

49. A computer program capable of performing the method of claim 14 embodied in a computer readable medium.

50. A computer program capable of performing the method of claim 15 embodied in a computer readable medium.

51. A computer program capable of performing the method of claim 16 embodied in a computer readable medium.

52. A computer program capable of performing the method of claim 17 embodied in a computer readable medium.

53. A computer program capable of performing the method of claim 18 embodied in a computer readable medium.

54. A computer program capable of performing the method of claim 19 embodied in a computer readable medium.

55. A computer program capable of performing the method of claim 20 embodied in a computer readable medium.

56. A computer program capable of performing the method of claim 21 embodied in a computer readable medium.

57. A computer program capable of performing the method of claim 22 embodied in a computer readable medium.

58. A computer program capable of performing the method of claim 23 embodied in a computer readable medium.

59. A computer program capable of performing the method of claim 24 embodied in a computer readable medium.

60. A computer program capable of performing the method of claim 25 embodied in a computer readable medium.

61. A computer program capable of performing the method of claim 26 embodied in a computer readable medium.

62. A computer program capable of performing the method of claim 27 embodied in a computer readable medium.

63. A computer program capable of performing the method of claim 28 embodied in a computer readable medium.

64. A computer program capable of performing the method of claim 29 embodied in a computer readable medium.

65. A computer program capable of performing the method of claim 30 embodied in a computer readable medium.

66. A computer program capable of performing the method of claim 31 embodied in a computer readable medium.

67. A computer program capable of performing the method of claim 32 embodied in a computer readable medium.

68. A computer program capable of performing the method of claim 33 embodied in a computer readable medium.

69. A computer program capable of performing the method of claim 34 embodied in a computer readable medium.

70. A computer program capable of performing the method of claim 35 embodied in a computer readable medium.

## ABSTRACT

- 5            Provided is a keystroke output wedge, implemented in software or firmware, that presents natural language messages to a user. The messages may be in text form on a display or transmitted in audible form to a wireless headset for example. The wedge provides data translation functions for devices used to collect and input data into a computer such as a bar code scanner. It can also provide messages to
- 10 the user of the data input device relating to the state of associated application programs and computer operating systems. The wedge can be programmed to provide prompts, such as "SCAN PART NUMBER," or feedback, such as "VALID SCAN."



Fig. 1




Fig. 2

200



**Transaction Definition**

Transaction Name: PURCHASE ORDER FULFILLMENT 202

Window Title: P.O. FILL 204

Initial Keystrokes: {SPACE BAR} 206

Transaction Prompt: F:\Source\Keyport\Sounds\POFILL.WAV 208

Editing field 1 of 3:

Field Name: Purchase Order NUMBER 210

Field Mask: PO~? 212

Exit Keystrokes: {TAB} 214

Audio Prompt: F:\Source\Keyport\Sounds\PO.WAV 216

Error Sound: F:\Source\Keyport\Sounds\BadPO.WAV 218


Previous Next New Delete Chars to Strip

Front: 0 Back: 0

OK Delete Transaction

220

302



	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
1	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
2	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	52	54	56	58	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88	90	92	94	96	98	100	102	104	106	108	110	112	114	116	118	120	122	124	126	128	130	132	134	136	138	140	142	144	146	148	150	152	154	156	158	160	162	164	166	168	170	172	174	176	178	180	182	184	186	188	190	192	194	196	198	200
3	3	6	9	12	15	18	21	24	27	30	33	36	39	42	45	48	51	54	57	60	63	66	69	72	75	78	81	84	87	90	93	96	99	102	105	108	111	114	117	120	123	126	129	132	135	138	141	144	147	150	153	156	159	162	165	168	171	174	177	180	183	186	189	192	195	198	201	204	207	210	213	216	219	222	225	228	231	234	237	240	243	246	249	252	255	258	261	264	267	270	273	276	279	282	285	288	291	294	297	300
4	4	8	12	16	20	24	28	32	36	40	44	48	52	56	60	64	68	72	76	80	84	88	92	96	100	104	108	112	116	120	124	128	132	136	140	144	148	152	156	160	164	168	172	176	180	184	188	192	196	200	204	208	212	216	220	224	228	232	236	240	244	248	252	256	260	264	268	272	276	280	284	288	292	296	300																									
5	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140	145	150	155	160	165	170	175	180	185	190	195	200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300																																								
6	6	12	18	24	30	36	42	48	54	60	6																																																																																									

PATENT

**DECLARATION AND POWER OF ATTORNEY  
IN PATENT APPLICATION**Attorney Docket No.: 1441-6

As a below named inventor, I hereby declare:

My residence, post office address and citizenship are as stated below next to my name.

Inventor is a small entity.

I believe that I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are listed below) of the subject matter that is claimed and for which a patent is sought on the invention entitled:

NATURAL LANGUAGE MESSAGES FROM A KEYSTROKE OUTPUT WEDGE

the specification of which

☒ is attached hereto.p was filed on \_\_\_\_\_ as U.S. Application Serial No.  
(or PCT International Application No.) \_\_\_\_\_  
and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b), of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT international application designating at least one country other than the United States listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

## Prior Foreign Application(s):

<u>Number</u>	<u>Country</u>	<u>Date Filed</u>	<u>Priority Claimed</u>
_____	_____	Day/Mo/Year	<input type="checkbox"/> Yes <input type="checkbox"/> No
_____	_____	Day/Mo/Year	<input type="checkbox"/> Yes <input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code Section 119(e) of any United States provisional application(s) listed below.

<u>Application No.</u>	<u>Filing Date</u>
_____	_____

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or Section 365(c) of any PCT international application designating the United States listed below, and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56, which became available between the filing date of the prior application and the national or PCT international filing date of this application.

<u>Application Number</u>	<u>Filing Date</u>	<u>Status: Patented/ Pending/Abandoned</u>
_____	_____	_____
_____	_____	_____
_____	_____	_____

I hereby appoint the attorneys associated with Customer No. 000996 to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith. Address all correspondence and phone calls to:

Jeffrey T. Haley  
 GRAYBEAL JACKSON HALEY LLP  
 155 - 108th Avenue NE, Suite 350  
 Bellevue, WA 98004-5901 USA  
 Telephone (425) 455-5575  
 Facsimile (425) 455-1046

I hereby further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Paul A. Bolme

United States

Full Name of Inventor

Citizenship

10307 Meridian Ave Everett, WA 98208  
Residence

Post Office Address (if different from Residence)

Paul A. Bolme  
Inventor's Signature

9-29-00  
Date

Mark Bolme

United States

Full Name of Inventor

Citizenship

7811 234<sup>th</sup> St. SW, Edmonds, WA 98026  
Residence

Post Office Address (if different from Residence)

Mark W. Bolme  
Inventor's Signature

9/29/00  
Date